



Any piece of equipment can be dangerous if not operated properly. You are responsible for the safe operation of this equipment. The operator must carefully read and follow any warnings, safety signs and instructions provided with or located on the equipment. Do not remove, defeat, deface or render inoperable any of the safety devices or warnings on this equipment. If any safety devices or warnings have been removed, defeated, defaced or rendered inoperable, **DO NOT USE THE EQUIPMENT!!!** If this equipment requires the use of diesel fuel: Diesel engine exhaust and some of its constituents are known to cause cancer, birth defects, and other reproductive harm.

ELECTROCUTION HAZARD! Check for overhead obstructions and high voltage power lines. A minimum distance of 10 feet from energized high voltage conductors shall be maintained at all times!

DO NOT OPERATE UNLESS AUTHORIZED AND TRAINED TO RUN LIFT!

1. Ensure that the aerial work platform is on a firm and level surface. Do not drive on soft or uneven terrain. Failure to take caution could cause lift to tip-over. The aerial work platform shall not be driven on grades, slide slopes or ramps exceeding those for which the aerial work platform is rated by the manufacturer.
2. Inspect the work area thoroughly for all obstacles, debris, drop-offs, holes, slopes and depressions.
3. Inspect the lift thoroughly before each use. Test all functions before raising platform. Check fluid levels, tire pressure, hoses for leaks, breaks in the cable and elevating assembly. **NEVER OPERATE A DAMAGED MACHINE!!!**
4. Ensure that all guard rails are properly secured and gates and opening are closed. Do not sit, stand, lean or place loads on guard rails.
5. Personnel shall maintain a firm footing in the basket at all times. Do not use ladders or other objects on the lift to gain greater height. **ALWAYS KEEP TWO FEET ON THE PLATFORM.**
6. Hard hat, safety glasses and safety shoes should always be worn by operator.
7. If unit has outriggers, do not raise platform until outriggers are extended fully and stabilizers are down.
8. Know the rated capacity of the aerial lift. Distribute the load evenly over the platform.
DO NOT OVERLOAD. SERIOUS INJURY COULD OCCUR.
9. Do not operate lift when the wind velocity exceeds 25 MPH or in thunderstorm conditions.
EXTREME WINDS COULD CAUSE THE LIFT TO TIP-OVER!
10. Do not drive with the platform raised! When raised, move only to maneuver!
11. Do not allow ropes, cords, etc., to become entangled in the elevating parts.
- 12. STUNT DRIVING AND HORSEPLAY COULD RESULT IN INJURY OR DEATH! BE SAFE!**
13. The operator is responsible for ensuring that all personal protective equipment is used.
14. The aerial platform shall not be used as a crane.
15. Before operating any aerial work platform, operators shall have read and be familiar with the operators manual and shall abide by the safety rules.

If the person receiving this handout will not be the user of the equipment, forward these instructions to operator. If there is any doubt as to the operation or safety of the equipment. **DO NOT USE!!! CALL US IMMEDIATELY!!!**

FAILURE TO FOLLOW THESE INSTRUCTIONS COULD RESULT IN INJURY OR DEATH

Date: _____

(Lessee's Signature)

(Print Name)

(Title)