


Specifications



MODELS	GS™-3390 RT		GS™-4390 RT		GS™-5390 RT	
MEASUREMENTS	US	Metric	US	Metric	US	Metric
Working height maximum*	39 ft	12.06 m	49 ft	15.11 m	59 ft	18.15 m
A Platform height maximum	33 ft	10.06 m	43 ft	13.11 m	53 ft	16.15 m
B Platform height - stowed**	5 ft 1 in	1.55 m	5 ft 11 in	1.80 m	6 ft 7.5 in	2.02 m
C Platform length:						
outside, extended - single deck	13 ft .5 in	3.98 m	13 ft .5 in	3.98 m	13 ft .5 in	3.98 m
outside, extended - dual deck	17 ft 6.25 in	5.34 m	17 ft 6.25 in	5.34 m	17 ft 6.25 in	5.34 m
D Slide-out platform extension deck - front	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m
E Slide-out platform extension deck - rear	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
F Platform width - outside	4 ft	1.22 m	4 ft	1.22 m	4 ft	1.22 m
G Height:						
stowed	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
stowed - rails lowered	8 ft 10.5 in	2.71 m	9 ft 7.5 in	2.93 m	10 ft 4 in	3.15 m
I Length - stowed:						
single deck	6 ft 7.75 in	2.03 m	7 ft 4.75 in	2.25 m	8 ft 1.25 in	2.47 m
dual deck	12 ft 11.25 in	3.94 m	12 ft 11.25 in	3.94 m	†	—
with outriggers	13 ft .5 in	3.98 m	13 ft .5 in	3.98 m	—	—
Length - extended:						
single deck	16 ft	4.88 m	16 ft	4.88 m	16 ft	4.88 m
dual deck	17 ft 8.5 in	5.40 m	17 ft 8.5 in	5.40 m	17 ft 8.5 in	5.40 m
J Width:						
standard tires	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m
high flotation tires	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m
K Wheelbase	8 ft 5 in	2.57 m	8 ft 5 in	2.57 m	8 ft 5 in	2.57 m
L Ground clearance - center	9 ft 4 in	2.84 m	9 ft 4 in	2.84 m	9 ft 4 in	2.84 m
	1 ft 2 in	.36 m	1 ft 2 in	.36 m	1 ft 2 in	.36 m

PRODUCTIVITY						
Maximum platform occupancy***	7	7	7	7	6	6
Lift capacity	2,500 lbs	1,134 kg	1,500 lbs	680 kg	1,500 lbs	680 kg
Lift capacity - extension deck	500 lbs	227 kg	500 lbs	227 kg	500 lbs	227 kg
Drive height	full height		full height		30 ft	9.14 m
Drive speed - stowed	5.0 mph	8.0 km/h	5.0 mph	8.0 km/h	5.0 mph	8.0 km/h
Drive speed - raised	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h
Gradeability - stowed****	50%		50%		40%	
Maximum outrigger leveling: front to back	7°		7°		7°	
side to side	12°		12°		12°	
Turning radius - inside	7 ft 1 in	2.16 m	7 ft 1 in	2.16 m	7 ft 1 in	2.16 m
Turning radius - outside	17 ft 6 in	5.33 m	17 ft 6 in	5.33 m	17 ft 6 in	5.33 m
Controls	proportional		proportional		proportional	
Drive	four wheel		four wheel		four wheel	
Raise / lower speed	45 / 29 sec		45 / 39 sec		55 / 49 sec	
Tires - foam-filled rough terrain	12 x 33 in	30 x 84 cm	12 x 33 in	30 x 84 cm	12 x 33 in	30 x 84 cm

POWER						
Power source	Ford DSG-423 4 cylinder gas/LPG 75 hp (56 kW) Deutz D2011L03i 3 cylinder diesel 49 hp (36 kW), air cooled					
Auxiliary Power unit	12 V DC		12 V DC		12 V DC	
Fuel tank capacity	30 gal	113.6 L	30 gal	113.6 L	30 gal	113.6 L
Hydraulic system capacity	30 gal	113.6 L	30 gal	113.6 L	30 gal	113.6 L

WEIGHT*****						
	12,085 lbs	5,482 kg	12,925 lbs	5,862 kg	†	—
with outriggers	13,760 lbs	6,241 kg	14,642 lbs	6,641 kg	16,698 lbs	7,574 kg

STANDARDS COMPLIANCE

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Based on RT tires. Deduct 2 in (5.8 cm) for high flotation air-filled and non-marking tires.

*** GS-5390 CE/AUS market limited to 4 person platform occupancy.

**** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

***** Weight will vary depending on options and/or country standards.

† GS-5390 comes standard with outriggers.

Machine length with outriggers represents overall length.

Features

STANDARD FEATURES

MEASUREMENTS

GS™-3390

- 39 ft (12.06 m) working height
- Up to 2,500 lb (1,134 kg) lift capacity

GS™-4390

- 49 ft (15.11 m) working height
- Up to 1,500 lb (680 kg) lift capacity

GS™-5390

- 59 ft (18.15 m) working height
- Up to 1,500 lb (680 kg) lift capacity

PRODUCTIVITY

- 156.5 x 72 in (3.98 x 1.83 m) steel frame platform
- 60 in (1.52 m) extension deck
- Replaceable aluminum deck
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Two self-closing gates
- 4WD
- Automatic leveling hydraulic outriggers
- Oscillating axle
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tires (eco fill)
- Tilt level sensor with audible alarm
- Descent alarm
- Horn
- Hour meter

POWER

- Deutz diesel 49 hp (36 kW)


OPTIONS & ACCESSORIES

PRODUCTIVITY OPTIONS

- Oscillating axle (standard on GS™-3390, optional on GS™-4390 and GS™-5390)
- Automatic leveling hydraulic outriggers (optional on GS™-3390 and GS™-4390, standard on GS™-5390)
- Dual slide-out platform extension deck package 5 ft (1.52 m) front and 4 ft (1.22 m) rear
- Air line to platform
- Non-marking rough terrain tires 12 x 33 (30 x 84 cm)
- High flotation air-filled tires 17 x 33 (43 x 84 cm)
- High flotation foam-filled tires 16 x 33 (41 x 84 cm)
- Dual flashing beacons
- Motion alarm

POWER OPTIONS

- Ford gas/LPG 75 hp (56 kW)
- Deutz diesel 49 hp (36 kW)
- 2000 AC Watt generator (120 V / 60 Hz)
- Cold weather package
- Hydraulic oil cooler
- Diesel scrubber/spark arrestor
- LPG steel tank only, 33.5 lb capacity



Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **+1 (425) 881-1800**
Toll Free in USA/Canada **+1 (800)-536-1800**
Fax +1 (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
UK

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: AWP-InfoEurope@terex.com

Distributed By:

Effective Date: April, 2011. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Brand. © 2011 Terex Corporation.

GS90RT 0210L. Part No. 109352

www.genieindustries.com